



Part Number EEG .00 . . . . .

**EEG.00.302.CLL**

Size/Series 00 / 00

[Request a quote](#)

**MECHANICAL DETAILS**

**Shell Style/Model** EE\*: Fixed receptacle, nut fixing (back panel mounting)  
 1 key (alpha=0, plug: male contacts, receptacle: female contacts)  
**Keying**  
**Housing Material** Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces  
**Cable Fixing** : 0 - 0 mm  
**Variant** :


	A	B	E	L	M	N	P	S1	S2	e
mm.	10	9.5	2.3	15.5	2.5	13.7	6	6.3	7.5	M7x0.5
in.	0.39	0.37	0.09	0.61	0.10	0.54	0.24	0.25	0.30	

**PERFORMANCE DETAILS**

**Insert Configuration** 0.302 : 2 Low Voltage  
**Insulator** L: PEEK  
**Specifications**  
**Contact Type:** Solder  
**Max. Matings:** 5000  
**Contact Dia.:** 0.5 mm (0.02in)  
**Bucket Dia.:** 0.4 mm (0.016in)  
**Max. Solid Conductor:** 0.09 mm<sup>2</sup> (AWG 28)  
**Max. Stranded Conductor:** 0.05 mm<sup>2</sup> (AWG 30)  
**R (max):** 8.7 mOhm  
**Vtest (contact-shell):** 950 V (AC), 1340 V (DC)  
**Vtest (contact-contact):** 1000 V (AC), 1400 V (DC)  
**Rated Current:** 5 A (AC/DC)

**OTHER CHARACTERISTICS**

**IP Rating** 50  
**Catalog**



[Copyright](#) [Privacy policy](#) [Product safety](#)

