



Part Number EEG .00 .304 .

EEG.00.304.CLL

Size/Series 00 / 00

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model EE*: Fixed receptacle, nut fixing (back panel mounting)
 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Keying
Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing : 0 - 0 mm
Variant :

	A	B	E	L	M	N	P	S1	S2	e
mm.	10	9.5	2.3	15.5	2.5	13.7	6	6.3	7.5	M7x0.5
in.	0.39	0.37	0.09	0.61	0.10	0.54	0.24	0.25	0.30	

PERFORMANCE DETAILS


Insert Configuration 0.304 : 4 Low Voltage
Insulator L: PEEK
Specifications
Contact Type: Solder
Max. Matings: 5000
Contact Dia.: 0.5 mm (0.02in)
Bucket Dia.: 0.4 mm (0.016in)
Max. Solid Conductor: 0.09 mm² (AWG 28)
Max. Stranded Conductor: 0.05 mm² (AWG 30)
R (max): 8.7 mOhm
Vtest (contact-shell): 650 V (AC), 920 V (DC)
Vtest (contact-contact): 800 V (AC), 1130 V (DC)
Rated Current: 2 A (AC/DC)

OTHER CHARACTERISTICS

IP Rating 50
Catalog



[Download 3D draw](#)



[Copyright](#) [Privacy policy](#) [Product safety](#)

