



Part Number

EGG.00.304.CLL

Size/Series 00 / 00

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model EG*: Fixed receptacle, nut fixing
Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing Variant : 0 - 0 mm

	A	B	E	L	M	N	S1	S3	e
mm.	8	10.3	6	15.5	1	13.7	6.3	9	M7x0.5
in.	0.31	0.41	0.24	0.61	0.04	0.54	0.25	0.35	

PERFORMANCE DETAILS


Insert Configuration 0.304 : 4 Low Voltage
Insulator L: PEEK
Specifications
Contact Type: Solder
Max. Matings: 5000
Contact Dia.: 0.5 mm (0.02in)
Bucket Dia.: 0.4 mm (0.016in)
Max. Solid Conductor: 0.09 mm² (AWG 28)
Max. Stranded Conductor: 0.05 mm² (AWG 30)
R (max): 8.7 mOhm
Vtest (contact-shell): 650 V (AC), 920 V (DC)
Vtest (contact-contact): 800 V (AC), 1130 V (DC)
Rated Current: 2 A (AC/DC)

OTHER CHARACTERISTICS

IP Rating Catalog 50



[Download 3D draw](#)



[Copyright](#) [Privacy policy](#) [Product safety](#)

