



Part Number  .  .  .

**FFA.00.250.CTAC27Z**

Size/Series 00 / 00

Demande d'offres

**MECHANICAL DETAILS**

**Shell Style/Model** FFA\*: Straight plug with cable collet and nut for fitting a bend relief




**Keying** Circular (can rotate)

**Housing Material** Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

**Cable Fixing** C27: 2.3 - 2.7 mm **NEW COLLET**

**Variant** Z : Nut for fitting a bend relief

	A	L	M
mm.	6.4	33.5	25.5
in.	0.25	1.32	1.00



**MECHANICAL DETAILS**

**Insert Configuration** 0.25 : 1 Coax (50 Ohm)

**Insulator** T: PTFE

**Specifications**

**Contact Type:** Coaxial 50 Ohm (Solder)

**Max. Matings:** 5000

**Contact Dia.:** 0.7 mm (0.028in)

**Bucket Dia.:** 0.6 mm (0.024in)

**R (max):** 6.1 mOhm

**Vtest:** 2100 V (AC), 3000 V (DC)

**Rated Current:** 4 A (AC/DC)

**Impedance:** 50 Ohm

**VSWR:** 1.09 + 0.11 \* f/GHz

**Cable type:** RG 316 /U

**MECHANICAL DETAILS**

**Endurance (Shell)** 3839 mating cycles

**F ret (min):** 100 N

**IP Rating** 50

**Catalog**

