



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: UPSRMR11

### Supports UPS systems in 4-post rackmount applications

#### Highlights

- Supports UPS systems in 4-post rackmount applications.
- Supports any rackmount chassis up to 250 lbs
- Includes 2 pairs of expandable "L bracket" mounting rails



#### Description

Tripp Lite's UPSRMR11 adjustable rackmount shelf system supports heavy UPS systems in 4 post rackmount applications. Two included pairs of expandable "L bracket" mounting rails offer front to rear support of any rackmount chassis up to 250 lbs. Supports UPS systems in 4 post rackmount applications. Pair of expandable "L brackets" adjust to any setting between 23.5 and 36.5 inches. Adding a 2nd UPSRMR11 enables back-to-back installation compatible with front to rear rail rack depths of 35.25 to 49.5 inches. Also compatible with other heavy pieces of networking or power protection equipment with 17.5 inch wide rectangular chassis.

#### Applications

- Ideal for supporting heavy networking and power protection equipment

#### Package Includes

- UPSRMR11 adjustable rackmount shelf kit
- Owner's manual

#### Features

- Supports UPS systems in 4 post rackmount applications
- Includes 2 pairs of expandable "L bracket" mounting rails offer front to rear support of any rackmount chassis up to 250 lbs.
- "L brackets" adjust to any setting between 23.5 and 36.5 inches
- A 2nd UPSRMR11 enables back-to-back installation compatible with front to rear rail rack depths of 35.25 to 49.5 inches
- Compatible with other heavy pieces of networking or power protection equipment with 17.5 inch wide rectangular chassis

#### Specifications

PHYSICAL	
Shipping weight (lbs)	5
Shipping weight (kg)	2.3

<b>Unit Dimensions (HWD/in)</b>	6.4 x 61.6 x 6
<b>Material of construction</b>	Steel
<b>Form factors supported</b>	Supports UPS systems in 4 post rackmount applications. Pair of expandable L brackets adjust to any setting between 23.5 and 36.5 inches. Adding a 2nd <a href="#">UPSRMR11</a> enables back-to-back installation compatible with front to rear rail rack depths of 35.25 to 4
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2630](http://www.tripplite.com/en/products/model.cfm?txtModelID=2630).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.