

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

15020-0213

Status:

Active

Overview:

Premo-Flex™ FFC and Etched Polyimide Jumpers

Description:

0.50mm Pitch Premo-Flex™ FFC Jumper, Same Side Contacts (Type A), 20 Circuits, 0.127m Cable Length, 0.27mm Cable Thickness, Gold (Au) Plating



Documents:

Drawing (PDF)

Product Specification PS-15020-001 (PDF)

Packaging Specification PK-15020-001 (PDF)

RoHS Certificate of Compliance (PDF)

|                               |                                              |
|-------------------------------|----------------------------------------------|
| General                       |                                              |
| Product Family                | Cable                                        |
| Series                        | 15020                                        |
| Comments                      | Contacts on the same side, Type A            |
| Crimp Quality Equipment       | Yes                                          |
| Overview                      | Premo-Flex™ FFC and Etched Polyimide Jumpers |
| Product Name                  | Premo-Flex™ FFC Jumper                       |
| UPC                           | 884982176751                                 |
| Physical                      |                                              |
| Cable Length                  | 0.127m                                       |
| Circuits (Loaded)             | 20                                           |
| Circuits (maximum)            | 20                                           |
| Net Weight                    | 0.833/g                                      |
| Packaging Type                | Bag                                          |
| Pitch - Termination Interface | 0.50mm                                       |
| Temperature Range - Operating | -40°C to +105°C                              |
| Wire Size AWG                 | N/A                                          |
| Wire/Cable Type               | Flat Flex Cable                              |
| Electrical                    |                                              |
| Current - Maximum per Contact | 0.5A                                         |
| Voltage - Maximum             | 60V AC                                       |
| Material Info                 |                                              |
| Reference - Drawing Numbers   |                                              |
| Packaging Specification       | PK-15020-001                                 |
| Product Specification         | PS-15020-001                                 |
| Sales Drawing                 | SD-15020-001                                 |

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

15020Series

Use With

[www.molex.com/product/ffcfpc\\_th.html](http://www.molex.com/product/ffcfpc_th.html)

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION