





		1		2		3		4	
	FCI PART NUMBER	DESCRIPTION	NOTES						
	10119217-XXXXLF	CONTROLLER TO BACKPLAN	NE SEE TABLE I						
Α	PADDLE CARD	ODIFIED POLYPHENYLENE E : PRINTED CIRCUIT SUBSTI TUBE: POLYOLEFIN TE							A
	2. THIS PRODUCT MEETS THE RESTRICTION OF HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT (R⊙HS) DIRECTIVE (2002/95/EC)								
	3. THIS DIMENSION IS A FINISHED PRODUCT LENGTH.								
В	4. UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE IS TO BE: "DIM L" < I METER = ±25mm "DIM L" METER TO 10 METERS = ± 2% OF "DIM L"								
	5. UNLESS OTHERWISE SPECIFIED LABEL POSITION IS TO BE 95mm FROM REAR OF PI CONNECTOR. LABEL DETAILS: MANUFACTURER CODE OR NAME COUNTRY OF ORIGIN								В
	CUSTOMER P/N OR FCI P/N REVISION DATE CODE (YYYY/MM/DD FORMAT) - SERIAL NUMBER								
	FONT SHALL BE CLEARLY VISIBLE AND BLACK IN COLOR.								
	6. ALL CABLE ASSEMBLIES SHALL BE 100% TESTED FOR CONTINUITY AS DEFINED IN WIRING LIST.								
	7. ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED BH APPLYING 300V DC FOR A MINUMUM OF 10ms.								
С	8. IMPEDANCE: 100Ω DIFFERENTIAL.								
	9. OTHER TESTING PERFORMED AS REQUIRED BY PRODUCT SPECIFICATION: GS-12-650.								
	10. PACKAGE AND LABEL CABLE ASSEMBLIES PER GS-14-1272.								
	II. A " " SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION. THE CURRENT REVISION WILL BE SHOWN IN THE SYMBOL.								С
	12. "HLF" PRODUCT NUMBERS DESIGNATE THE USE OF HALOGEN FREE RAW CABLE.								
	13. HALOGEN FREE RAW CABLE CAN BE USED AS A SUBSTITUTE ON NON-HF PRODUCT NUMBERS.								
	14. PART NUMBER/SUPPLIER SUBSTITUTION IS NOT ALLOWED.								_
-	15. THIS PRODUCT CONFORMS TO THE MECHANICAL DIMENSIONING AND ELECTRICAL REQUIREMENTS OF THE SFF-8643 SPECIFICATION.								
50 -									
<u> </u>									
D				pec ref - olerance std	d r David Lord e n g Jason Gu	2011/12/14 projec	_ mm	1 1	cale P:I
				ISO 406 ISO 1101 TOLERANCES U OTHERWISE SPE	JNLESS L. L. Kouin Bai	2013/05/16 product f		ecn no El	ELX-N-14778-1
surface $-/$ linear $0.XX \pm 0.10$ FC) \pm mSAS HD INTERNAL (4i)								rel level	r e v
	Pro/E File - REV C - 2009-06-09				± 0.005 $\pm 2^{\circ}$ www.fci.com co	CABLE ASSEMBLY- 12 Gb/s t.no	Product - Custome	r Drw sheet	

2

Copyright FCI.

PDS: Rev :D

STATUS:Released

Printed: May 17, 2013

3