



## **SPECIFICATIONS**

- Shielded Badge Holder
  - $_{\circ}$  Material Thickness: .028" (.71mm) back and .012" (.30mm) (3H) badge holder
  - Material Tolerance (thickness): ±10%
- Includes a 1/8" (3mm) x 9/16" (14mm) punch through slot and two 3/16" (5mm) diameter hang holes located along the top
- Includes a clear vinyl pocket to secure the card when it is not being scanned
- Insert Size: 2-1/4" (57mm) x 3-1/2" (89mm)
- Outer Dimensions: 2-3/4" (70mm) x 5-1/4" (133mm)
- Opening along the top of card pocket
- Embossed with "ShieldID" and "Made In America" along card header

Dimensional tolerances are ±1/16" unless specified.



## **FEATURES**

- FIPS 201 Approved Approved Products List (APL) #577
- Shields 13.56 Mhz RFID technology smart cards including MIFARE, iClass, PIV, CAC, TWIC, and FRAC
- Protects smart cards against information and identity theft
- No need to remove the card from the holder. Simply flip it away from the shield to transmit the card's data. Release the card and the magnet will pull it right back to its protected state.
- · Made of durable, lightweight vinyl
- Made in the United States of America



Specification and procedures subject to change without notice.

## SHIELD ID II VINYL BADGE HOLDER, 2-1/4" (57MM) x 3-1/2" (89MM) INSERT SIZE

3651 WALNUT AVENUE, CHINO, CA 91710 PHONE: (909) 627-2453 FAX: (951) 755-8848

WEBSITE: Menda-ID.com

DRAWING NUMBER

35008

September 2011