

Cables



Industrial Cat. 5 stranded cable, 8-wire, PVC, Outdoor
to make up flexible connections
(one- or two-sided assembled system cables)

IP 20	<input checked="" type="checkbox"/>	IP 65 / IP 67	<input checked="" type="checkbox"/>	PVC	Cat. 5	<input checked="" type="checkbox"/>	Cat. 6	<input type="checkbox"/>
-------	-------------------------------------	---------------	-------------------------------------	-----	--------	-------------------------------------	--------	--------------------------

Cable structure	4 x 2, Twisted Pair, shielded
Core structure	4 x 2 x AWG 26/7
Wire insulation	PE, Ø 1.0 mm
Sheath material	PVC
Cable sheath diameter	6.5 mm ... 6.9 mm
Transmission performance	Category 5 / Class D up to 100 MHz according to ISO/IEC 11 801:2002, EN 50 173-1
Transmission rate	10/100/1000 Mbit/s
Shielding	Foil screen and additional plaited cable
Operating temperature range	–10 °C ... +60 °C
Standard lengths	20 m / 50 m / 100 m / 500 m
Colour	Black
Advantages	Robust design suitable for industry Applicable also for outside applications UL, AWM style 2969 Flame retardant Weather proof UV resistant RoHS compliant With Fast Connect inside sheath

Identification	Part number	Drawing	Dimensions in mm
Industrial Cat. 5 stranded cable, 8-wire, outdoor PVC 20 m ring 50 m ring 100 m ring 500 m drum	09 45 600 0230 09 45 600 0240 09 45 600 0200 09 45 600 0220		