

PCB LAYOUT - COMPONENT VIEW

TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR MATERIAL: PBT
FLAMMABILITY RATING UL94-V0
COLOUR: BLACK
CONTACT MATERIAL: COPPER ALLOY
CONTACT TYPE: STAMPED
CONTACT PLATING: GOLD
SHIELDING: BRONZE NI PLATED
QUALITY CLASS: 500 MATING CYCLES

ENVIRONMENTAL
OPERATING TEMPERATURE: -25°C UP TO 85°C
COMPLIANCE: LEAD FREE AND ROHS


ELECTRICAL
CURRENT RATING: 1.5 A
WORKING VOLTAGE: 120 VAC
INSULATION RESISTANCE: >500 MOHM
DIELECTRIC WITHSTANDING VOLTAGE: 1 000 VAC/MN
CONTACT RESISTANCE: 20 mOHM MAX

SOLDERING
WAVE PROCESS ONLY

PACKAGING
TRAY

RoHS Compliant

PROJECTION:



GENERAL TOLERANCE

.X = ± 0.2

.XX = ± 0.15



APPROVAL: RJ

UNIT: MM

SCALE:

SHEET: 1/1




DRAW:

DESCRIPTION: HORIZONTAL PLASTIC 4P4C MODULAR JACK
TAP UP

WERI PART NO: 615 004 143 821

SIZE

A4

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = ± 0.2 .XX = ± 0.15		DESCRIPTION: HORIZONTAL PLASTIC 4P4C MODULAR JACK TAP UP	SIZE A4
G								
F								
E								
D								
C				APPROVAL: RJ	UNIT: MM SCALE: SHEET: 1/1 DRAW:		DESCRIPTION: HORIZONTAL PLASTIC 4P4C MODULAR JACK TAP UP	SIZE A4
B								
A	03-NOV-08	PDF	CH					
REV	DATE	FILE	BY					