



TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: NYLON 66
FLAMABILITY RATING: UL94-V0
COLOR: BEIGE
PITCH: 2.54MM

ENVIRONMENTAL
OPERATING TEMPERATURE: -40 UP TO 105°C
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
INSULATOR RESISTANCE: >1000 MOHM
DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC/MN

STANDARD
 CERTIFIED: E323964

PACKAGING
BAG

DIMENSION

PINS	A
2	5.60
3	8.10
4	10.70
5	13.20
6	15.80
8	20.90
10	25.90
12	31.00
14	36.10

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = $\pm$ 0.2 .XX = $\pm$ 0.15		
G							
F	06-AUG-13	CHARACTERISTIC	QL				
E	17-NOV-09	STANDARD	JP				
D	30-JAN-06	DRAW	EC	APPROVAL: RJ	UNIT: MM SCALE: SHEET: 1/1 DRAW: PEARL	DESCRIPTION: 2.54 MM FEMALE TERMINAL HOUSING WERI PART NO: 6190xx11621	SIZE A4
C	30-MAR-04	LEAD FREE	JP				
B	19-MAR-04		JP				
A	17-JUL-02	PDF	JP				
REV	DATE	FILE	BY				