



# 714

## Combustion Analyzer with NO / NOx

### Features

**QUICK AND SIMPLE SET UP** All TPI analyzers feature quick and simple set up. Fast purge and the ability to perform fuel selection during start up enable tests to be performed quickly without requiring extra set-up time after initial start-up. TPI analyzers also use the last selected fuel as the default setting. This feature prevents the need to perform fuel selection every time the analyzer is turned on.

- Built-in differential manometer with 0.001" H<sub>2</sub>O resolution
- Measure NO (Nitric Oxide), Calculate NO<sub>x</sub>
- Calculates combustion efficiency
- Data Logging with time and date stamp
- Will not shut off if 15 ppm CO is present for increased safety
- Communicate to a PC via the optional A767 IR interface
- Optional A740 IR printer available for hard copies of test results
- Built-in differential thermometer
- Store function to save up to 50 readings
- Pump driven for fast response
- Push on fittings for fast and easy use
- Large easy to read backlit display
- Ten selectable fuels

### Specifications

#### Instrument

Operating Temperature Range	14°F to +122°F (-10°C to +50°C)
Battery / Battery Life	Rechargeable Ni-MH / > 6 Hours
Charger Input Voltage	115V or 230V : 50/60 Hz AC
Fuels	Natural Gas, LPG, Light Oil, Heavy Oil, Bituminous Coal, Anthracite Coal, Coke, Butane, Wood, Bagasse
Units of Pressure	mbar, kPa & inH <sub>2</sub> O
Display	3 Line Backlit LCD w/ annunciators
Data Storage	50 sets of readings
Data Logging	400 sets of readings
Single Logging	150 sets of readings
Time & Date	24 Hour Real Time Clock
Dimensions	7.8" x 3.5" x 2.4"
Weight	1.1lbs

#### Gases

	Range	Resolution	Accuracy
Oxygen	0-25%	0.1%	+/- 0.3%
Carbon Monoxide	0-10,000 ppm	1 ppm	+/- 5 ppm or 5%
Nitric Oxide	0-5,000ppm	1 ppm	+/- 5 ppm to 5%
Carbon Dioxide	0-25%	0.1%	Calculated
NOX	0-5250ppm	1 ppm	Calculated
CO/CO <sub>2</sub> Ratio	0-0.999	0.001	Calculated
Combustion Eff.	0-100%	0.1%	Calculated

#### Pressure Measurement

Selectable Ranges	mbar, kPa and inH <sub>2</sub> O
Range	-120 inH <sub>2</sub> O to 120 inH <sub>2</sub> O
Resolution	0.001 inH <sub>2</sub> O
Accuracy	+/- 0.5% fsd

#### Temperature Measurement

Input Type	K-Type thermocouple
Range	-58°F to 1832°F (-50°C to 1000°C)*
Resolution	1°F (1°C)
Accuracy	+/- (0.3% of rdg + 2°F) or +/- (0.3% of rdg + 1°C)

### 714 Contents

#### 714 Combustion Analyzer



#### A787 Soft Carrying Case



#### A603 Brass Hose Barb Fitting (2)



#### A774 Silicone Tubing



#### A763 Mini pump protection filter



#### A776 Static Tip (2)



#### A770 Flue Probe



#### A791 Adapter tubing



#### GK11M K-type thermocouple



#### A611 Gas Valve Pressure Adapter

