






A B C D E F

| | | |
|------|----|----------|
| DATE | BY | REVISION |
| | | |



BEIGE

INSULATOR MATERIAL
 :PBT, UL 94V-0
 CONTACT MATERIAL
 :Brass, Gold Plated Over Nickel
 SHELL FINISH
 :Nickel Silver
 OVERMOLD MATERIAL
 :PVC
 CURRENT RATING
 :0.5mA
 DIELECTRIC STRENGTH
 :1000V AC for one minute
 INSULATOR RESISTANCE
 :1000M Ω min at 500V DC

CONFIGURATION:
 A MALE A MALE

- 1 _____ 1
- 2 _____ 2
- 3 _____ 3
- 4 _____ 4
- G _____ G

| | | | |
|-------|-------------|----------|---------|
| DATE | 17 JAN,2003 | PARTS NO | |
| UNIT | MM | DRAWN NO | A-USB-5 |
| SCALE | | BUYER NO | 002 |

TITLE:

ADAPTER
 USB A MALE/MALE
A-USB-5

| | | |
|-------|---------------|-------|
| DRAWN | Y.C.C 1/17 | CHECK |
|-------|---------------|-------|

ASSMANN ELECTRONICS.INC

| |
|-------|
| APPRO |
|-------|