


	1	2	3	4	5	6	7																																																													
A						Material		A																																																												
B						Terminal body(Contact pin): Brass Wire guard:Stainless steel Surface of Solder tail:Tin plated Terminal (housing): Thermoplastic (UL94V-0) , GREEN		B																																																												
C						Electrical cULus/VDE Voltage rating: 300VAC/450VAC Current rating: 10A/10A Wire range: 0.75-1.5mm² Solid wire(AWG): 14-24 Stranded wire(AWG): 14-24 Pull force: Screw: Wire strip length: 9-10mm Withstanding Voltage: 1.6KV/2.5KV Operating temperature: -40°C to +115°C Soldering temperature: 250°C±10°C/5 Sec Safety Approval:  		C																																																												
D								D																																																												
E								E																																																												
F						DIMENSION		F																																																												
					<table border="1"><tr><td>L</td><td>Nx10.0</td></tr><tr><td>P</td><td>(N-1)x10.0</td></tr></table>		L	Nx10.0	P	(N-1)x10.0	<table border="1"><thead><tr><th rowspan="2">Poles</th><th colspan="2">Tolerance</th></tr><tr><th>DIM L</th><th>DIM P</th></tr></thead><tbody><tr><td>2p-6p</td><td>±0.15</td><td>±0.10</td></tr><tr><td>7p-12p</td><td>±0.20</td><td>±0.20</td></tr><tr><td>13p-18p</td><td>±0.30</td><td>±0.25</td></tr><tr><td>19p-24p</td><td>±0.40</td><td>±0.30</td></tr></tbody></table>		Poles	Tolerance		DIM L	DIM P	2p-6p	±0.15	±0.10	7p-12p	±0.20	±0.20	13p-18p	±0.30	±0.25	19p-24p	±0.40	±0.30	N=Number of poles																																						
L	Nx10.0																																																																			
P	(N-1)x10.0																																																																			
Poles	Tolerance																																																																			
	DIM L	DIM P																																																																		
2p-6p	±0.15	±0.10																																																																		
7p-12p	±0.20	±0.20																																																																		
13p-18p	±0.30	±0.25																																																																		
19p-24p	±0.40	±0.30																																																																		
G	RECOMMENDER PCB LAYOUT							G																																																												
RoHS compliant					<table border="1"><tr><td>Scale</td><td>1:1</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td rowspan="2">Customer-No.</td></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>19.04.2010</td><td>Alex</td></tr></table>		Scale	1:1					Date	Name	Customer-No.	TOLERANCE						Drawn	19.04.2010	Alex	ASSMANN WSW-No. A-TB100-HAxxV																																											
					Scale	1:1					Date	Name	Customer-No.																																																							
TOLERANCE						Drawn	19.04.2010	Alex																																																												
<table border="1"><tr><td>X.</td><td>±0.50</td><td></td><td></td><td></td><td></td><td>Approved</td><td>19.04.2010</td><td>Hellwig</td></tr><tr><td>X.X</td><td>±0.30</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±0.10</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.°</td><td>±1°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td>Ⓢ</td><td>Drawn</td><td>19.04.2010</td><td>Alex</td><td colspan="2"></td><td>Drawing-No.</td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="2">Replace</td><td>rev00</td></tr></table>		X.	±0.50					Approved	19.04.2010	Hellwig	X.X	±0.30								X.XX	±0.10								DIM	TOL								X.°	±1°										Ⓢ	Drawn	19.04.2010	Alex			Drawing-No.	Angle	TOL	Id.	Modification	Date	Name	Replace		rev00	ASS 4122 CO		Sheet	
X.	±0.50					Approved	19.04.2010	Hellwig																																																												
X.X	±0.30																																																																			
X.XX	±0.10																																																																			
DIM	TOL																																																																			
X.°	±1°																																																																			
		Ⓢ	Drawn	19.04.2010	Alex			Drawing-No.																																																												
Angle	TOL	Id.	Modification	Date	Name	Replace		rev00																																																												
H								H																																																												
	1	2	3	4	5	6	7																																																													