

Part Number: C0516A

Revision Level: 1

Date: 10/25/2007

3 PR 24 7/32 TC FMPP OAS PVC

Computer Cable

A. CONSTRUCTION

DIAMETERS

Conductor:	#24 AWG 7/32 Tinned Copper	0.024" nom.
Insulation:	0.016" Wall Foamed Polypropylene	0.056" nom.
Pairing	2 conductors @ 2.00" LHL	0.111" nom.
Cable:	3P @ 2.50" LHL with AL / PE & # 24 7/32 TC DW	0.204" nom.
Braid	# 36 AWG Tinned Copper 65% Min. Coverage	0.226" nom.
Jacket:	0.032" Wall Polyvinyl Chloride - Gray	0.290" +/- 0.015"
Print Legend:	<i>CAROL (R) 24 AWG -- C0516A -- 75C E111240-8 CM (UL) C (UL) CMH OR 80C AWM STYLE 2919 30V LOW VOLTAGE COMPUTER CABLE --- MADE IN USA (DATE CODE) (PRINT</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM(UL)c(UL) CMH
UL Subject 758	AWM Style 2919

C. ELECTRICAL PROPERTIES

TEMPERATURE:	80C
SUGGESTED WORKING VOLTAGE (Vrms):	30V
CONDUCTOR D.C. RESISTANCE:	25.7 Ohms/1000 ft nom
SHIELD RESISTANCE:	3.2 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	9.89 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	17.8 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	131.9 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Wht/Blu – Blu/Wht
2	Wht/Org – Org/Wht
3	Wht/Grn – Grn/Wht