

Part Number: C0660A

Revision Level: 00

Date: June 20, 2005

12.5P 22 7/30 TC SR-PVC OAS PVC

COMPUTER CABLE

A. CONSTRUCTION

DIAMETERS

1)	CONDUCTOR:	#22 AWG 7/30 Tinned Copper	0.030" nom.
2)	INSULATION:	0.010" Wall Semi Rigid Polyvinyl Chloride	0.050" nom.
3)	COLOR CODE:	1. Black-Red 2. Black-White 3. Black-Green 4. Black-Blue 5. Black-Yellow 6. Black-Brown 7. Black-Orange 8. Red-White 9. Red-Green 10. Red-Blue 11. Red-Yellow 12. Red-Brown Single Conductor: Green/Yellow	
4)	TWIN:	24 Conductors into 12 Pairs @ 2" LHL	0.100" nom.
5)	CABLE:	12 Pairs and 1 Conductor @ 5.00" LHL with aluminum/polypropylene (foil out)	0.336" nom.
6)	BRAID:	Tinned Copper Braid 65% Nom. Coverage	0.365" nom.
7)	JACKET:	0.032" Wall Polyvinyl Chloride – Gray	0.429" +/- 0.021"
8)	PRINT LEGEND:	CAROL (R) 22 AWG - - C0660A - - 75C E111240-8 CMR(UL)C(UL) OR 80C AWM STYLE 2464 300V--- CSA LL69381 CMG - - MADE IN USA (DATE CODE- -PRINT EVERY 3 FEET)	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CMR(UL)C(UL)
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

1)	TEMPERATURE:	75 C
2)	SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
3)	CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft. nom. @ 20 C
4)	SHIELD RESISTANCE:	4.7 Ohms/1000 ft. nom. @ 20 C
5)	MUTUAL CAPACITANCE:	26.2 Pf/ft. @ 1kHz nom.
6)	GROUND CAPACITANCE:	47.2 Pf/ft. @ 1kHz nom.
7)	CHARACTERISTIC IMPEDANCE:	76 Ohms @ 1 MHz nom.

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.