



PRODUCT DATA SHEET



Part Number: C2105A

Revision Level: 01

Date: April 23, 2008

1C 14 41/30 TC PVC INS

HOOK-UP WIRE

A. CONSTRUCTION

DIAMETERS

- | | | | |
|----|---------------|--|-------------------|
| 1) | CONDUCTOR: | #14 AWG 41/30 Tinned Copper | 0.077" nom. |
| 2) | INSULATION: | 0.032" Wall Polyvinyl Chloride | 0.141" +/- 0.007" |
| 3) | PRINT LEGEND: | <i>CAROL (R) 14 AWG - C2105A - RU AWM STYLE 1015 -- 105C VW-1 600V
E18621-8 - CSA TEW 105C LL69381 - MADE IN USA (RU is UL recognized logo)</i> | |

B. INDUSTRY APPROVALS

UL Subject 758

AWM Style 1015

CSA International

Type TEW

C. ELECTRICAL PROPERTIES

- | | | |
|----|-----------------------------------|--------------------------------|
| 1) | TEMPERATURE: | 105 C |
| 2) | SUGGESTED WORKING VOLTAGE (Vrms): | 600Vrms |
| 3) | CONDUCTOR D.C. RESISTANCE: | 2.81 Ohms/1000 ft. nom. @ 20 C |

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.