

Part Number: C2463A

Revision Level: 6

Date: 7/13/2007

4C 24 7/32 TC SR-PVC PVC
COMMUNICATION CABLE
A. CONSTRUCTION
DIAMETERS

Conductor:	#24 AWG 7/32 Tinned Copper	0.024" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.044" nom.
Cable:	4 conductors with mylar wrap	0.110" nom.
Jacket:	0.032" Wall Polyvinyl Chloride	0.174" +/- 0.009"
Print Legend:	CAROL (R) 24 AWG -- C2463A -- 75C E111240-8 CM (UL) C(UL) OR AWM STYLE 2464 & 2576 --- CSA LL69381 CMG -- MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000'	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (Vrms):	300 Vrms
CONDUCTOR D.C. RESISTANCE:	25.7 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	23 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green