

# General Cable Product Data Sheet

Part Number: C3310

Revision Level: 0

Date: 7/7/2007

**3C 22 7/30 TC OAS FLEX PVDF**

**TYPE CL2P**

## **A. CONSTRUCTION**

## **DIAMETERS**

Conductor:	#22 AWG 7/30 Tinned Copper	0.030" nom.
Insulation:	0.006" Wall FLEXGUARD*	0.042" nom.
Cable:	3 conductors @ 2.50" LHL w/ AL/Polypro (foil out)	0.096" nom.
Jacket:	0.010" Wall PVDF – Natural -Plenum ripcord under jacket.	0.116" +/- 0.006"
Print Legend:	<b><i>CAROL (R) 22 AWG -- C3310 -- 60C E60233-8 CL2P (UL) -- MADE IN USA DATE CODE (PRINT EVERY 2 FT)</i></b>	

## **B. INDUSTRY APPROVALS**

National Electrical Code  
UL Standard 13

Article 725  
Type CL2P

## **C. ELECTRICAL PROPERTIES**

TEMPERATURE:	60C
SUGGESTED WORKING VOLTAGE (Vrms):	150 Vrms (CL2P)
CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft. nom. @ 20C

## **D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

\*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.