

Part Number: C4064A

Revision: 10/15/2012

5C 22 AWG (7/30)TC PVC, PVC

COMMUNICATION & CONTROL CABLE

A. CONSTRUCTION

| | | |
|-------------|--|-----------|
| Conductor: | #22 AWG (7/30) Tinned Copper | .029" Nom |
| Insulation: | .010" Semi-Rigid Polyvinyl Chloride (SR-PVC) | .049" Nom |
| Cable Core: | Cable 5/C @ 4.00" LHL | .132" Nom |
| Jacket: | .032" Polyvinyl Chloride (PVC) jacket | .196" Nom |

Print Legend: **CAROL (R) 22 AWG -- C4064A -- 75C E105765-H CM (UL) C(UL) OR
AWM STYLE 2464 -- CSA LL69381 CMG 60C -- ROHS -- MADE IN USA
(DATE CODE) (SEQUENTIAL FOOTAGE)**

DIAMETERS

B. INDUSTRY APPROVALS

| | |
|--------------------------|-------------------------------|
| National Electrical Code | Article 800 |
| UL Standard 444 | Type CM |
| UL Standard 758 | AWM Style 2464 |
| CSA International | Type CMG |
| UL Standard 1581 | SUNLIGHT RESISTANT (720 HOUR) |

C. ELECTRICAL PROPERTIES

| | |
|----------------------------|--------------------------------|
| Temperature: | -20C to +80C |
| Suggested Working Voltage: | 300V Max |
| Conductor DCR: | 16.9 Ohms/1000 ft @ 20°C (nom) |
| Mutual Capacitance: | 24.5 pF/ft @ 1kHz (nom) |

D. COLOR CODE

| ITEM | COLOR |
|------|-------|
| 1 | BLACK |
| 2 | WHITE |
| 3 | RED |
| 4 | GREEN |
| 5 | BROWN |