

Description: Tinned Copper conductor, FEP Insulation, conductors cabled, overall foil shield and FEP Jacketed Plenum Cable.


A. Construction:

- 1.0 Primaries:
- 1.1 Conductor: 18 AWG
 Stranding 19/30 Tinned Copper;
 Nom. Dia .048"
- 1.2 Insulation: FEP
 Material FEP
 Nom. thickness .007"
 Nom. OD .062"
- 1.3 No. of conductors 4
- 1.4 Color code Black, White, Red, Green
- 2.0 Overall Cabling: 4 conductors cabled
- 3.1 Separator: Polyester tape
- 3.2 Shield: Aluminum/Polyester Tape; 100% coverage; (Aluminum Side out)
- 3.3 Drain Wire: 20 AWG Stranded Tinned Copper
- 3.0 Jacket Material: FEP Nom. wall: .014" Color: Red, or as requested
- 4.0 Overall Diameter of Cable Nom. .185"
- 5.0 Marking: Surface Print:
 GENERAL CABLE (F) C8114 4C 18 AWG SHIELDED CMP (UL) C(UL) ---- ROHS
 AAAAAA*
 * Indicates Shop Order number

B. Characteristics:

- 1.0 Conductor DC Resistance @20C Max. (Ohm): 5.5
- 2.0 Capacitance between conductors Nom. (pF/ft): 30
- 3.0 Capacitance Cond. To other Cond.& Shield Nom. (pF/ft): 55
- 4.0 Shield Resistance Nom.(Ohms/1000'): 7.9
- 5.0 Operating Voltage Nom.: 300 V
- 6.0 Continuous Operating Temp: 200C
- 7.0 Min. Bend Radius (inches): 1.8
- 8.0 Max. Pulling Tension Lbs: 114

C. Approvals: UL -CMP ; C(UL) CMP

R E V	DATE	CHANGE DETAIL			<div>General Cable</div> <div>20 Forge Park, Franklin, Ma 02038</div> <div>Phone: 508-541-7100 Fax: 508-541-8122</div>		
			Title:	C8114			
			Description:	4C 18 AWG Shielded Plenum Cable			
			Created By:				
A	07/02/09	Initial Release -DB	Final Approval:	VM - 7/2/09		PAGE 1 of 1	