

Part Number: E3032S

Revision: 8/6/2013

2C 18 AWG PVC, UNSH, PVC**SOUND, ALARM AND SECURITY CABLE****A. CONSTRUCTION**

Conductor: #18 AWG (7/26) Bare Copper .046" Nom
Insulation: .008" Wall, Plenum PVC .062" Nom
Cable Assembly: 2C with a 6.00" LHL .124" Nom
Ripcord: Plenum ripcord
Jacket: .015" Wall, Plenum PVC .154" ± .008"
Print Legend: **CAROL (R) 18 AWG -- E3032S -- 75C E60233-8 (UL) CL3P -- C(UL) CMP -- ROHS --
MADE IN USA (date code - MM/YY) (sequential footage)**
Sequential Footage: Yes.

DIAMETERS**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 13	Type CL3P
National Electrical Code	Article 800
UL Standard 444	Type CMP

C. ELECTRICAL PROPERTIES

Temperature: 0° to 75°C
Suggested Working Voltage: 300 Vrms (Max)
Conductor DCR: 6.66 Ohms/1000ft @ 20°C (Max)
Capacitance (Cond-Cond): 32.4 pF/ft. @ 1 kHz (Nom)
Characteristic Impedance: 60 Ohms @ 1MHz (Nom)

D. COLOR CODE

COND	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____
Date: _____