

General Cable Product Data Sheet

Part Number: E3504S

Revision Level: 4

Date: 10/26/2007

4C 18 SOLID BC FLEX FLEX

Fire Alarm/Life Safety Cable

A. CONSTRUCTION

DIAMETERS

Conductor:	#18 AWG Solid Bare Copper	0.040" nom.
Insulation:	0.010" Wall FLEXGUARD*	0.060" nom.
Cable:	4C @ 4.00" LHL	0.145" nom.
Jacket:	0.015" Wall FLEXGUARD* - Red	0.175" +/- 0.009"
Print Legend:	CAROL (R) 18 AWG - - E3504S - - 75C TYPE FPLP E66267-8 (UL) - - MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000' TO 0')	

B. INDUSTRY APPROVALS

National Electrical Code
UL Standard 1424

Article 760
Type FPLP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V
CONDUCTOR D.C. RESISTANCE:	6.39 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	33.44 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	60.8 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red
3	Brown
4	Blue

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.