

Part Number

FFA.0S.303.CLAC32

Size/Series 0S / S

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model	FFA*: Straight plug, cable collet
Keying	Hermaphroditic keying ("half moon" insert), plug has male pin 1
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	C32: 2.3 - 3.2 mm
Variant	:

NEW COLLET



	A	C	L	M	S2
mm.	9	4.2	34.5	24.5	6.5
in.	0.35	0.17	1.36	0.96	0.26

PERFORMANCE DETAILS

Insert Configuration	0S.303 : 3 Low Voltage
Insulator	L: PEEK
Specifications	
Contact Type:	Solder
Max. Matings:	5000
Contact Dia.:	0.7 mm (0.028in)
Bucket Dia.:	0.6 mm (0.024in)
Max. Solid Conductor:	0.25 mm ² (AWG 24)
Max. Stranded Conductor:	0.14 mm ² (AWG 26)
R (max):	6.1 mOhm
Vtest:	1060 V (AC), 1500 V (DC)
Rated Current:	7 A (AC/DC)

OTHER CHARACTERISTICS

Endurance (Shell)	3839 mating cycles
Humidity (max):	<=95% [at 60 deg C /140 F]
Vibration:	15 g [10 Hz - 2000 Hz]
Shock Resistance:	100 g [6 ms]
Salt Spray Corrosion:	>144 hr
Climatical Category:	50/175/21
Shielding (min):	75 dB (10 MHz)
Shielding (min):	40 dB (1 GHz)
IP Rating	50
Catalog	

[Download 3D draw](#)[Copyright](#) [Privacy policy](#) [Product safety](#)