

GA342D1XGF100JY02#

"	#	77	indicates a	a p	backage	specifi	cation	code.
---	---	-----------	-------------	-----	---------	---------	--------	-------

Recommended Reflow OK With RoHS	
< List of part numbers with package codes > GA342D1XGF100JY02L	
Shape	
	Notes
	Y2 Class Certified Products, IEC60950 Devices only

References

Packaging	Specifications	Minimum quantity	
L	180mm Embossed taping	2000	

L size	4.5 ±0.3mm
W size	2.0 ± 0.2mm
T size	2.0 ± 0.2mm
External terminal width e	0.3mm min.
Distance between external terminals g	2.5mm
Size code in inch(mm)	1808 (4520)

Specifications

Capacitance	10pF ±5%
Rated voltage	250Vac(r.m.s.)
Temperature characteristics (complied standard)	SL(JIS)
Temperature coefficient	+350 to -1000ppm/
Temperature range of temperature characteristics	20 to 85
Operating temperature range	-55 to 125

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/30