


GA343QR7GD182KW01#

| " | # | " | indicates | а | package | specification | code. |
|---|---|---|-----------|---|---------|---------------|-------|
|---|---|---|-----------|---|---------|---------------|-------|

Reflow OK Complies with RoHS Recommended < List of part numbers with package codes > GA343QR7GD182KW01L Shape Notes Y3 Class Certified Products, IEC60950 Devices only



References

| Packaging | Specifications | Minimum quantity |
|-----------|-----------------------|------------------|
| L | 180mm Embossed taping | 1000 |

| L size | 4.5 ± 0.4mm |
|---------------------------------------|---------------|
| W size | 3.2 ± 0.3mm |
| T size | 1.5 +0/-0.3mm |
| External terminal width e | 0.3mm min. |
| Distance between external terminals g | 2.5mm |
| Size code in inch(mm) | 1812 (4532) |

Specifications

| Capacitance | 1800pF ±10% |
|--|----------------|
| Rated voltage | 250Vac(r.m.s.) |
| Temperature characteristics (complied standard) | X7R(EIA) |
| Capacitance change rate | ± 15% |
| Temperature range of temperature characteristics | -55 to 125 |
| Operating temperature range | -55 to 125 |

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/30