

GA355XR7GB563KW06#

1	ŧ	"	indicates	а	package	specification	code.
---	---	---	-----------	---	---------	---------------	-------

Recommended Complies Reflow OK with RoHS	
< List of part numbers with package codes > GA355XR7GB563KW06L	
Shape	Notes
	X2 Class Certified Products

References

Packaging	Specifications	Minimum quantity	
L	180mm Embossed taping	500	

L size	5.7 ±0.4mm
W size	5.0 ± 0.4mm
T size	2.9 +0/-0.4mm
External terminal width e	0.3mm min.
Distance between external terminals g	3.0mm
Size code in inch(mm)	2220 (5750)

Specifications

Capacitance	56000pF ±10%
Rated voltage	250Vac(r.m.s.)
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/12/16