

# GCJ188R71H223KA01#



Notes

References


Packaging

"#" indicates a package specification code.

Resin external electrode products

# < List of part numbers with package codes > GCJ188R71H223KA01D , GCJ188R71H223KA01J

#### Shape





1.6 ±0.2mm
0.8 ±0.1mm
0.8 ±0.1mm
0.2 to 0.5mm
0.5mm min.
0603 (1608)

### Specifications

Capacitance	22000pF ±10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

Mass (typ.)		
J	330mm Paper taping	10000
D	180mm Paper taping	4000

Specifications

(yp.)	
1 piece	6.3mg
180mm Reel	144g

1 of 1

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/12/03

Minimum quantity