GCJ216R71H223KA01#


"#" indicates a package specification code.





< List of part numbers with package codes > GCJ216R71H223KA01D , GCJ216R71H223KA01J

Shape



	L size	2.0 ± 0.3mm
	W size	1.25 ± 0.2mm
	T size	0.6 ± 0.1mm
	External terminal width e	0.2 to 0.7mm
	Distance between external terminals g	0.7mm min.
	Size code in inch(mm)	0805 (2012)

Specifications

Capacitance	22000pF ±10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

Notes

Resin external electrode products

References

Packaging	Specifications	Minimum quantity
D	180mm Paper taping	4000
J	330mm Paper taping	10000

Mass (typ.)	
1 piece	9.6mg
180mm Reel	142g

1 of 1

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



muRata Murata Manufacturing Co., Ltd.

URL: http://www.murata.co.jp/

Last updated: 2013/12/03