

GCJ216R71H682KA01#



Notes

References


"# " indicates a package specification code.

Resin external electrode products

< List of part numbers with package codes >

GCJ216R71H682KA01D , GCJ216R71H682KA01J

Shape





0 ±0.3mm
25 ±0.2mm
.6 ±0.1mm
2 to 0.7mm
7mm min.
805 (2012)

Specifications

Capacitance	6800pF ±10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

Packaging Specifications D 180mm Paper taping 4000

D	roomin Paper taping	4000
J	330mm Paper taping	10000

Minimum quantity

Mass (typ.)	
1 piece	9.6mg
180mm Reel	142g

1 of 1

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/12/03