

## GCJ219R72A333KA01#



"# " indicates a package specification code.

< List of part numbers with package codes > GCJ219R72A333KA01D , GCJ219R72A333KA01J Notes Resin external electrode products References Packaging Specifications Minimum quantity D 180mm Paper taping 4000 330mm Paper taping 10000 J Mass (typ.)  $2.0 \pm 0.3$ mm 1 piece 11mg  $1.25 \pm 0.2 mm$ 180mm Reel 162g  $0.85 \pm 0.1 \text{mm}$ 

0.2 to 0.7mm

0.7mm min.

0805 (2012)

## Specifications

External terminal width e

Size code in inch(mm)

Distance between external terminals g

Shape

L size

W size

T size

Capacitance	33000pF ±10%
Rated voltage	100Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

1	of	1

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/12/05