GCJ21BR71C225KA13#

"#" indicates a package specification code.






0.2 to 0.7mm

0.7mm min.

0805 (2012)

< List of part numbers with package codes > GCJ21BR71C225KA13L , GCJ21BR71C225KA13K

Shape



N	Of	6	c

Resin external electrode products

References

Packaging	Specifications	Minimum quantity	
L	180mm Embossed taping	3000	
K	330mm Embossed taping	10000	

Mass (typ.)			
1 piece	17mg		
180mm Reel	102g		

Specifications

External terminal width e

Size code in inch(mm)

Distance between external terminals g

Capacitance	2.2μF ± 10%
Rated voltage	16Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

1 of 1

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



muRata Murata Manufacturing Co., Ltd.

URL: http://www.murata.co.jp/

Last updated: 2013/12/03