

GCJ32QR72E683KXJ1#

Deflecting crack Reflow OF © Complies with RoHS Recommended

< List of part numbers with package codes > GCJ32QR72E683KXJ1L

Shape

L size	3.2 ±0.3mm
W size	2.5 ± 0.2mm
T size	1.5 +0/-0.3mm
External terminal width e	0.3mm min.
Distance between external terminals g	1.2mm
Size code in inch(mm)	1210 (3225)

Specifications

Capacitance	68000pF ± 10%
Rated voltage	250Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

Packaging	Specifications	Minimum quantity
L	180mm Embossed taping	2000

"# " indicates a package specification code.

References

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/12/06