

GCM0335C1E2R4CD03#

"# " indicates a package specification code.

References

Packaging

D

J


180mm Reel

Ultra-Available UOMPIIes with RoHS

< List of part numbers with package codes >

 $\mathsf{GCM0335C1E2R4CD03D}\ ,\ \mathsf{GCM0335C1E2R4CD03W}\ ,\ \mathsf{GCM0335C1E2R4CD03J}$

Shape



|--|

 0.3 ± 0.03 mm

0.1 to 0.2mm

0.2mm min.

0201 (0603)

W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm		30000		
Mass (typ.)					
1 piece		0.33mg			

118g

Specifications

180mm Paper taping

330mm Paper taping

Minimum quantity

15000

50000

Specifications

External terminal width e

Size code in inch(mm)

Distance between external terminals g

T size

Capacitance	2.4pF ±0.25pF
Rated voltage	25Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

1	of	2
---	----	---

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




URL : http://www.murata.co.jp/

Last updated: 2013/11/16

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)







AC voltage characteristics







Capacitance - temperature characteristics



2 of 2

This PDF data has only typical specifications because there is no space for detailed specifications.

Therefore, please reviewour product specifications or consult the

approval sheet for product specifications before ordering.



Last updated: 2013/11/16