

## GCM32A7U2J122JX01#

Reflow OF Complies with RoHS Recommended

< List of part numbers with package codes > GCM32A7U2J122JX01D

## Shape

L size	3.2 ± 0.2mm
W size	2.5 ± 0.2mm
T size	1.0 +0/-0.3mm
External terminal width e	0.3mm min.
Distance between external terminals g	1.5mm
Size code in inch(mm)	1210 (3225)

## Specifications

Capacitance	1200pF ±5%
Rated voltage	630Vdc
Temperature characteristics (complied standard)	U2J(EIA)
Temperature coefficient	-750 ± 120ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

Reference	S
-----------	---

"#" indicates a package specification code.

Packaging	Specifications	Minimum quantity
D	180mm Paper taping	4000

	1	of	1
--	---	----	---

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/16