Capacitor data sheet

GQM2195C2A6R8DB01#

" # " indicates a package specification code.

Recommended | Flow OK | Reflow OK | Complies with RoHS | HIQ

< List of part numbers with package codes >
GQM2195C2A6R8DB01D , GQM2195C2A6R8DB01J

Shape



L size	2.0 ±0.1mm
W size	1.25 ±0.1mm
T size	0.85 ±0.1mm
External terminal width e	0.2 to 0.7mm
Distance between external terminals g	0.7mm min.
Size code in inch(mm)	0805 (2012)

References

Packaging	Specifications	Minimum quantity
D	φ180mm Paper taping	4000
J	φ330mm Paper taping	10000

Mass (typ.)	
1 piece	9.5mg
φ180mm Reel	152g

Specifications

Capacitance	6.8pF ±0.5pF
Rated voltage	100Vdc
Temperature characteristics (complied standard)	C0G(EIA)
Temperature coefficient	0±30ppm/℃
Temperature range of temperature characteristics	25 to 125℃
Operating temperature range	-55 to 125℃

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Murata Manufacturing Co., Ltd. URL : http://www.murata.co.jp/

Last updated: 2013/11/16

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

- Frequency characteristics (ESR, Impedance)



- S parameter (Smith chart S11)



- AC voltage characteristics



- Capacitance - temperature characteristics



This PDF data has only typical specifications because there is no space for detailed specifications.
Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering.

Murata Manufacturing Co., Ltd.
Last updated: 2013/11/16