Capacitor data sheet

GQM22M5C2H820GB01#

“ # ” indicates a package specification code.

Recommended | Reflow OK | Complies with RoHS | HIQ

< List of part numbers with package codes >
GQM22M5C2H820GB01L , GQM22M5C2H820GB01K

Shape



L size	2.8 ±0.5mm
W size	2.8 ±0.4mm
T size	1.15 ±0.2mm
External terminal width e	0.3mm min.
Distance between external terminals g	1.0mm min.
Size code in inch(mm)	1111 (2828)

Specifications

Capacitance	82pF ±2%
Rated voltage	500Vdc
Temperature characteristics (complied standard)	C0G(EIA)
Temperature coefficient	0±30ppm/℃
Temperature range of temperature characteristics	25 to 125℃
Operating temperature range	-55 to 125℃

References

Packaging	Specifications	Minimum quantity
L	φ180mm Embossed taping	1000
K	φ330mm Embossed taping	4000

Mass (typ.)	
1 piece	41mg
φ180mm Reel	73g

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Murata Manufacturing Co., Ltd. URL : http://www.murata.co.jp/

Last updated: 2013/12/04

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

- Frequency characteristics (ESR, Impedance)



- S parameter (Smith chart S11)



- AC voltage characteristics



- Capacitance - temperature characteristics



- Calorific property by ripple current



This PDF data has only typical specifications because there is no space for detailed specifications.
Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering.

Murata Manufacturing Co., Ltd.
Last updated: 2013/12/04