


GR355XD72W564KW05#

"#" indicates a package specification code.

Reflow OF Complies with RoHS Recommended

< List of part numbers with package codes > GR355XD72W564KW05L

Shape





o		 D' I	^ ·

Large Capacitance and High Allowable Ripple Current

References

Notes

Packaging	Specifications	Minimum quantity	
L	180mm Embossed taping	500	

L size	5.7 ± 0.4mm
W size	5.0 ± 0.4mm
T size	2.7 +0/-0.3mm
External terminal width e	0.3mm min.
Distance between external terminals g	3.2mm
Size code in inch(mm)	2220 (5750)

Specifications

Capacitance	$0.56\mu F \pm 10\%$
Rated voltage	450Vdc
Temperature characteristics (complied standard)	X7T(EIA)
Capacitance change rate	+22/-33%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/24