


GRM0335C1E430JD01#

To be Complies Ultradiscontinued Reflow OK with RoHS compact

< List of part numbers with package codes >

GRM0335C1E430JD01D , GRM0335C1E430JD01W , GRM0335C1E430JD01J

Shape





"#" indicates a package specification code.

L size	0.6 ± 0.03mm
W size	0.3 ± 0.03mm
T size	0.3 ± 0.03mm
External terminal width e	0.1 to 0.2mm
Distance between external terminals g	0.2mm min.
Size code in mm(inch)	0603 (0201)
Specifications	
Capacitance	43pF ±5%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

Notes

Please use replacements or Recommended.

References

Pac	skaging Spe	ecifications	Minimum quantity
D	180mm Paper taping	150	00
J	330mm Paper taping	500	00
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	300	00
		Mass (typ.)	

	Mass (typ.)	
1 piece		0.33mg
180mm Reel		118g

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

1 of 1