


## GRM0336S1E430JD01#

Reflow OK Ultra-compact To be discontinued © Complies with RoHS

< List of part numbers with package codes >

 $\mathsf{GRM0336S1E430JD01D}\ ,\ \mathsf{GRM0336S1E430JD01W}\ ,\ \mathsf{GRM0336S1E430JD01J}$ 

## Shape



L size	0.6 ±0.03mm
W size	0.3 ±0.03mm
T size	0.3 ±0.03mm
External terminal width e	0.1 to 0.2mm
Distance between external terminals g	0.2mm min.
Size code in inch(mm)	0201 (0603)

## Specifications

Capacitance	43pF ±5%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	S2H(EIA)
Temperature coefficient	-330 ± 60ppm/
Temperature range of temperature characteristics	25 to 85
Operating temperature range	-55 to 125

Packaging	Specifications	Minimum quantity
D	180mm Paper taping	15000
J	330mm Paper taping	50000
W	180mm Paper taping (W8P1*)	30000

\* Width : 8mm, Pocket pitch : 1mm

"#" indicates a package specification code.

References

Mass (typ.)	
1 piece	0.33mg
180mm Reel	118g

1 of 1

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/13