


GRM0336S1E7R2CD01#

Reflow OK Ultra-compact To be discontinued Complies with RoHS

< List of part numbers with package codes >

 $\mathsf{GRM0336S1E7R2CD01D}\ ,\ \mathsf{GRM0336S1E7R2CD01W}\ ,\ \mathsf{GRM0336S1E7R2CD01J}$

Shape



 0.3 ± 0.03 mm

0.1 to 0.2mm

0.2mm min.

0201 (0603)

"#" indicates a package specification code.

References

Packaging

D	180mm Paper taping	15000		
J	330mm Paper taping	50000		
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	30000		
Mass (typ.)				

Specifications

Minimum quantity

Mass (typ.)	
1 piece	0.33mg
180mm Reel	118g

Specifications

External terminal width e

Size code in inch(mm)

Distance between external terminals g

T size

Capacitance	7.2pF ±0.25pF
Rated voltage	25Vdc
Temperature characteristics (complied standard)	S2H(EIA)
Temperature coefficient	-330 ± 60ppm/
Temperature range of temperature characteristics	25 to 85
Operating temperature range	-55 to 125

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/13