


GRM0337U1H7R8CD01#

Reflow OK Ultra-compact To be discontinued Complies with RoHS

< List of part numbers with package codes >

 $\mathsf{GRM0337U1H7R8CD01D}\ ,\ \mathsf{GRM0337U1H7R8CD01W}\ ,\ \mathsf{GRM0337U1H7R8CD01J}$

Shape





L size	0.6 ±0.03mm
W size	0.3 ±0.03mm
T size	0.3 ±0.03mm
External terminal width e	0.1 to 0.2mm
Distance between external terminals g	0.2mm min.
Size code in inch(mm)	0201 (0603)

Specifications

Capacitance	7.8pF ±0.25pF
Rated voltage	50Vdc
Temperature characteristics (complied standard)	U2J(EIA)
Temperature coefficient	-750 ± 120ppm/
Temperature range of temperature characteristics	25 to 85
Operating temperature range	-55 to 125

#"	indicates	а	package	specification	code.
----	-----------	---	---------	---------------	-------

References

Minimum quantity Packaging Specifications D 180mm Paper taping 15000 330mm Paper taping 50000 J 180mm Paper taping (W8P1*) W 30000 * Width : 8mm, Pocket pitch : 1mm

Mass (typ.)				
1 piece	0.33mg			
180mm Reel	118g			

1 of 1

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/13