

GRM033R71E271KA01#

“ # ” indicates a package specification code.

Available


Reflow OK

Complies with RoHS

Ultra-compact

< List of part numbers with package codes >
GRM033R71E271KA01D , GRM033R71E271KA01W , GRM033R71E271KA01J

Shape



L size	0.6 ± 0.03mm
W size	0.3 ± 0.03mm
T size	0.3 ± 0.03mm
External terminal width e	0.1 to 0.2mm
Distance between external terminals g	0.2mm min.
Size code in mm(inch)	0603 (0201)

Specifications

Capacitance	270pF ± 10%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

References

Packaging		Specifications	Minimum quantity
D	180mm Paper taping		15000
J	330mm Paper taping		50000
W	180mm Paper taping (W8P1*)		30000
		* Width : 8mm, Pocket pitch : 1mm	

	Mass (typ.)	
1 piece	0.33mg	
180mm Reel	118g	

 Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.