## GRM033R71E391KA01#

"#" indicates a package specification code.






< List of part numbers with package codes >

GRM033R71E391KA01D , GRM033R71E391KA01W , GRM033R71E391KA01J

## Shape





L size  $0.6 \pm 0.03$ mm W size  $0.3 \pm 0.03$ mm  $0.3 \pm 0.03$ mm T size External terminal width e 0.1 to 0.2mm 0.2mm min. Distance between external terminals g Size code in mm(inch) 0603 (0201)

## Specifications

Capacitance 390pF ± 10% 25Vdc Rated voltage X7R(EIA) Temperature characteristics (complied standard) Capacitance change rate ± 15.0% Temperature range of temperature characteristics -55 to 125 Operating temperature range -55 to 125

## References

	Packaging	Specifications	Minimum quantity
D	180mm Paper taping		15000
J	330mm Paper taping		50000
W	180mm Paper taping (W8P1*)  * Width: 8mm, Pocket pitch: 1mm		30000
		Mass (typ.)	
1 pi	iece	0.33r	ng
18	80mm Reel	118g	

1 of 1



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

multata Murata Manufacturing Co., Ltd.

URL: http://www.murata.co.jp/

Last updated: 2013/10/23