

GRM1535C1H8R0DDD5#


"#" indicates a package specification code.

References

Reflow OK To be discontinued Complies with RoHS

< List of part numbers with package codes > GRM1535C1H8R0DDD5D , GRM1535C1H8R0DDD5J

Shape



- P	

 0.3 ± 0.03 mm

0.1 to 0.3mm

0.4mm min.

0402 (1005)

Packaging	Specifications	Minimum quantity
D	180mm Paper taping	10000
J	330mm Paper taping	50000

Mass (typ.)	
1 piece	1.0mg
180mm Reel	88g

Specifications

External terminal width e

Size code in inch(mm)

Distance between external terminals g

T size

Capacitance	8.0pF ± 0.5pF
Rated voltage	50Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




URL : http://www.murata.co.jp/

Last updated: 2013/11/13

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)







AC voltage characteristics







Capacitance - temperature characteristics



2 of 2

This PDF data has only typical specifications because there is no space for detailed specifications.

Therefore, please reviewour product specifications or consult the

approval sheet for product specifications before ordering.



Last updated: 2013/11/13