

GRM1555C1E2R4BZ01#

"#" indicates a package specification code.


Notes

To be discontinued Reflow OF omplies with RoHS

< List of part numbers with package codes >

 $\mathsf{GRM1555C1E2R4BZ01D}\ ,\ \mathsf{GRM1555C1E2R4BZ01W}\ ,\ \mathsf{GRM1555C1E2R4BZ01J}$

Shape



References Specifications Packaging Minimum quantity D 180mm Paper taping 10000 330mm Paper taping 50000 J

Please use replacements or Recommended.

W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	20000

Mass (typ.)		
1 piece	1.6mg	
180mm Reel	118g	

Specifications

Capacitance	2.4pF ± 0.1pF
Rated voltage	25Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/13