

GRM1555C1H151JA01#


"#" indicates a package specification code.

Recommended Reflow OK With RoHS

< List of part numbers with package codes >

GRM1555C1H151JA01D , GRM1555C1H151JA01W , GRM1555C1H151JA01J

Shape





L size	1.0 ± 0.05mm
W size	0.5 ±0.05mm
T size	0.5 ± 0.05mm
External terminal width e	0.15 to 0.35mm
Distance between external terminals g	0.3mm min.
Size code in mm(inch)	1005 (0402)
Specifications	
Capacitance	150pF ±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

References

Pack	aging Sp	ecifications Minimum quantity	
D	180mm Paper taping	10000	
J	330mm Paper taping	50000	
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	20000	
		Mass (typ.)	
1 piece		1.6mg	

180mm Reel

1 of 2

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata Murata Manufacturing Co., Ltd.


118g

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


Frequency characteristics (ESR, Impedance)




AC voltage characteristics



This PDF data has only typical specifications because there is no space for detailed specifications. Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering. S parameter (Smith chart S11)



Capacitance - temperature characteristics





Last updated: 2013/10/23