

GRM1555C1H1R1CZ01#


"#" indicates a package specification code.

To be Complies discontinued Reflow OK

< List of part numbers with package codes >

 $\mathsf{GRM1555C1H1R1CZ01D}\ ,\ \mathsf{GRM1555C1H1R1CZ01W}\ ,\ \mathsf{GRM1555C1H1R1CZ01J}$

Shape





L size	1.0 ± 0.05mm
W size	0.5 ± 0.05mm
T size	0.5 ± 0.05mm
External terminal width e	0.15 to 0.35mm
Distance between external terminals g	0.3mm min.
Size code in mm(inch)	1005 (0402)
Specifications	
Capacitance	1.1pF ± 0.25pF
Rated voltage	50Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125
Notes	
Please use replacements or Recommended.	
References	

Packag	ing	Specifications	Minin	num quantity
D	180mm Paper taping		10000	
J	330mm Paper taping		50000	
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm		20000	
		Moss (twp.)		

	Mass (typ.)	
1 piece		1.6mg
180mm Reel		118g

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering. 1 of 1