

GRM1555C1H1R6CZ01#

" # " indicates a package specification code.


To be discontinued

Reflow OK

Complies with RoHS

< List of part numbers with package codes >
GRM1555C1H1R6CZ01D , GRM1555C1H1R6CZ01W , GRM1555C1H1R6CZ01J

Shape



L size	1.0 ± 0.05mm
W size	0.5 ± 0.05mm
T size	0.5 ± 0.05mm
External terminal width e	0.15 to 0.35mm
Distance between external terminals g	0.3mm min.
Size code in mm(inch)	1005 (0402)

Specifications

Capacitance	1.6pF ± 0.25pF
Rated voltage	50Vdc
Temperature characteristics (complied standard)	C0G(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

Notes

Please use replacements or Recommended.

References

Packaging		Specifications	Minimum quantity
D	180mm Paper taping		10000
J	330mm Paper taping		50000
W	180mm Paper taping (W8P1*)		20000
		* Width : 8mm, Pocket pitch : 1mm	

		Mass (typ.)
1 piece		1.6mg
180mm Reel		118g

⚠ Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.