

GRM1555C1H3R6CZ01#


"#" indicates a package specification code.

To be Complies discontinued Reflow OK

< List of part numbers with package codes >

 $\mathsf{GRM1555C1H3R6CZ01D}\ ,\ \mathsf{GRM1555C1H3R6CZ01W}\ ,\ \mathsf{GRM1555C1H3R6CZ01J}$

Shape





L size	1.0 ± 0.05mm	
W size	0.5 ± 0.05mm	
T size	0.5 ± 0.05mm	
External terminal width e	0.15 to 0.35mm	
Distance between external terminals g	0.3mm min.	
Size code in mm(inch)	1005 (0402)	
Specifications		
Capacitance	3.6pF ± 0.25pF	
Rated voltage	50Vdc	
Temperature characteristics (complied standard)	COG(EIA)	
Temperature coefficient	0 ± 30ppm/	
Temperature range of temperature characteristics	25 to 125	
Operating temperature range	-55 to 125	
Notes		
Please use replacements or Recommended.		
References		

Packaging		Specifications	Minimun	n quantity
D	180mm Paper taping		10000	
J	330mm Paper taping		50000	
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm		20000	
		Mass (typ.)		

	Mass (typ.)	
1 piece		1.6mg
180mm Reel		118g

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

1 of 1